



Tirana, 15.07.2016

CONFIRMATION LETTER

Herewith, University of New York Tirana, confirms that the following equipment to be purchased in the framework of the Erasmus + project with the title "**Strategic Support on Strengthening the Quality Assurance Structures at the Private Higher Education Institutions in Albania**", project no. **561510-EPP-1-2015-1-AT-EPPKA2-CBHE-JP**, funded by the Erasmus + Programme of the European Union.

No	Description of the item	Quantity
1	Computer CPU: Intel® Core™ i7 (4790) Intel® Integrated Graphics: AMD Radeon™ R7 250, 2GB, Half Height, (DP and DVI-I) RAM: 16GB DDR3 SDRAM at 1600Mhz - 2 DIMMS HDD: 1000GB2 SATA hard drive Keyboard: USB Keyboard; Mouse: USB Mouse	40
2	Monitor 19" (19-inch viewable image size) Aspect Ratio: Standard (5:4) Optimal resolution: 1280 x 1024 at 60 Hz Contrast Ratio: 1000: 1 (typical) Brightness: 250 cd/m2 (typical) Max Viewing Angle: (178° vertical / 178° horizontal) Color Support: 16.7 million colors Pixel Pitch: 0.29mm Panel Backlight: LED	40
3	UPS Batteries, Power Tree Input: 130-300 Vac Frequency: 50/60 Hz (+/-10%) Output Voltage: 220V(+/-10%) Output Power: 650VA; Output Power – Max: 700VA Output Voltage: 220Volt(+/-10%) Max. Output Current: 1.5A Output Frequency: 50/60Hz(+/-5%) Load Backup: >25Minute Low Battery Automatic Cut-off & Automatic Restart: Yes	45

	Capacity(Joule): 520	
4	<p>ProSafe 48-Port Smart Gigabit Switch w/ 2x Combo Ports & 2x SFP Ports</p> <p>Forty-Eight (48) 10/100/1000 Mbps ports which deliver full-speed packet forwarding</p> <p>Includes 2 combo and 2 SFP ports which provide optional fibre connectivity for greater distance</p> <p>Compatible with Windows, MAX and Linux operating systems</p> <p>Simple to set up and simple to use for effortless network monitoring and troubleshooting</p> <p>Smart Switch capability enabling key management features for the value price of an unmanaged switch</p>	2
5	<p>Slide Changer</p> <p>Dimensions (height x width x depth): 1.49 in (37.8 mm) x 4.55 in (115.5 mm) x 1.08 in (27.4 mm)</p> <p>Weight: 2.01 oz (57 g)</p> <p>Receiver Dimensions (height x width x depth): 0.65 in (16.5 mm) x 2.31 in (58.6 mm) x 0.31 in (7.9 mm)</p> <p>Receiver Weight: 0.21 oz (6 g)</p> <p>Color: Black</p> <p>Laser Class: Class 2 Laser</p> <p>Max Output: Less than 1mW</p> <p>Wave Length: 640~660nm (red light)</p> <p>Battery type: 2 AAA batteries</p> <p>Battery life (Laser pointer): 20-hour maximum</p> <p>Battery life (Presenter): 1050-hour maximum</p> <p>Wireless operating distance: Approx 10m*</p> <p>Wireless technology: 2.4 GHz wireless technology</p> <p>Supported OS: Windows Vista, Windows 7, Windows 8</p> <p>Interface: USB</p>	12
6	<p>Printer laser</p> <p>Print Technology: Monochrome Laser</p> <p>Processor: Dual Core, 800 MHz</p> <p>Memory, Standard: 128 MB</p> <p>Packaged Size (in. - H x W x D): 15.0 x 17.0 x 18.6 in.</p> <p>Packaged Weight (lb.): 34.85 lb.</p> <p>Size (in. - H x W x D): 10.3 x 15.7 x 15.0 in.</p> <p>Weight (lb.): 30.9 lb.</p> <p>Noise Level, Idle: 15 dBA</p> <p>Noise Level (Print), Operating: 53 dBA</p> <p>Duplex Print Noise Level, Operating: 52 dBA</p> <p>Laser Cartridge Yields (up to)4:</p> <p>1,500-page Cartridge</p> <p>5,000-page Black High Yield Cartridge</p>	1

	Paper Output Capacity, Maximum: Up to 150 pages 20 lb or 75 gsm bond	
7	<p>Router</p> <p>CPU nominal frequency: 1.2 GHz</p> <p>SFP DDMI: Yes</p> <p>CPU core count: 36</p> <p>Architecture : TILE</p> <p>Size of RAM: 4 GB</p> <p>10/100/1000 Ethernet ports: 12</p> <p>Number of USB ports: 1</p> <p>Power Jack: 1</p> <p>Supported input voltage: 13 V - 30 V</p> <p>Voltage Monitor: Yes</p> <p>CPU temperature monitor: Yes</p> <p>PCB temperature monitor: Yes</p> <p>Dimensions: 355x145x55cm</p> <p>Operating System: RouterOS v6 (64bit)</p> <p>Tested ambient temperature: -20C .. +60C</p> <p>CPU: TLR4-03680CG-12CE-A3b</p> <p>Max Power consumption: 69W</p> <p>SFP ports: 4</p> <p>Serial port: RS232</p> <p>Storage type: NAND</p> <p>Storage size: 1 GB</p>	1
8	<p>Multimedia headset</p> <p>Noise-cancelling Clear Voice Technology (CVT)</p> <p>Premium sound at all volume levels</p> <p>Anisotropic ferrite magnet structures deliver high sensitivity and reduced sound distortion</p> <p>Experience absolute comfort with soft, leatherette ear Cushions</p> <p>Impedence: 100 ohms (headset); Frequency: 8-20,000 Hz</p> <p>103dB SPL/1mW</p>	20
9	<p>Multimedia Speakers</p> <p>Speaker Type: 2.1</p> <p>Power Type: AC</p> <p>Power Rating (RMS): 60 watts; Satellite: 2 x 15 watts (into 8 ohms, @1 KHz, @10% THD); Subwoofer: 30 watts (into 4 ohms, @100Hz, @10% THD)</p> <p>Power Adapter: 100 - 240V (50/60Hz)</p> <p>Connections: Inputs: Stereo RCA, 3.5 mm auxiliary inputs</p> <p>Headphone jack: 3.5 mm</p> <p>Driver Size: Satellite: 2.6 in (66 mm) full range phase plug speaker drivers; Subwoofer: 5.25 in (133 mm) front-firing dome driver</p>	1

	<p>Sound Pressure Level (SPL Max): >97 dBA Signal -to-Noise Ratio (SNR): Satellites: 80 dB, A-weighted Subwoofer: 80 dB, A-weighted Frequency response: 55 Hz – 20 kHz Input Impedance: 8Kohm Audio Controls: Bass,Volume,ON/OFF on control pod Sensitivity: Satellites: 450mV;Subwoofer: 200mV</p>	
10	<p>Black hard drives Interface: SATA 6 Gb/s Form Factor: 3.5 Inch RPM Class: 4 TB Cache: 64 MB</p>	2
11	<p>Projector Brightness: 3,000 Lumens; Contrast(Full On/Off): 13,000:1 Native Resolution: 1024x768; Aspect Ratio: 4:3 (XGA) Data Modes: MAX 1920x1200; 3D Modes: PC 3D Ready Digital Inputs:HDMI; HDBaseT: No Max Power: 235 Watts; Voltage:100V - 240V Weight: 2.5 kg Lamp Life(Full Power): 5,000 hours; Lamp Life(eco-mode): 6,000 hours Lamp Type: Osram; Lamp Wattage: 190 Watts Lamp Quantity: 1 Display Type: DLP (1) Audible Noise:31.0 dB</p>	11
12	Cable Management – CAT 5E (1 box of 350m)	1

I, the undersigned, declared that have read and accepted as described and confirmed the need for equipment.



ANDREAS GALATOULAS
CEO

Address: Rr "Kodra e Diellit" Tirana, Albania

Tel: +355 44 5 12345

Website: www.unyt.edu.al